

## AGRIMAX RT 855 - Spécifications techniques



### Description

AGRIMAX RT 855 est un pneu caractérisé par une excellente traction et un grand confort. Il est conçu essentiellement pour le travail de la terre et les déplacements tant dans les champs que sur la route; certaines tailles sont également adaptées pour les applications de pulvérisation et le vendange. AGRIMAX RT 855 possède des excellentes qualités d'auto-nettoyage qui permettent de passer rapidement du travail aux champs aux déplacements sur route.

### UM

International Standard

### Construction

RADIAL

### Machinery

Agriculture: Pulvérisateur , Tracteur , Machine à vendanger

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 380/85 R 24<br>(14.9 R 24) |
| LI/SS     | 131 A8/B                   |

### Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Section Width (mm)         | 380            |
| Overall Diameter (mm)      | 1256           |
| Static Loaded Radius (mm)  | 554            |
| Rolling Circumference (mm) | 3720           |
| Rim Rec                    | W 12           |
| Rim Alt                    | W 11 ; W 13    |
| ECE                        | E4-106R-000592 |
| TRA Code                   | R1W            |

Load capacity (Kg)

| km/h / bar | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 50         | 1075 | 1250 | 1425 | 1600 | 1775 | 1950 |
| 40         | 1075 | 1250 | 1425 | 1600 | 1775 | 1950 |
| 30         | 1150 | 1340 | 1530 | 1715 | 1905 | 2090 |
| 10 LT      | 1440 | 1675 | 1910 | 2145 | 2380 | 2615 |
| 10 HT      | 1150 | 1340 | 1530 | 1715 | 1905 | 2090 |

Printed on 20/05/2021 11:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..