

## MP 567 - Spécifications techniques



### Description

MP 567 est un pneu agro-industriel adapté tant pour le transport aux champs que sur route, pour les opérations dans le cadre des services municipaux de voirie. Le pneu MP 567 offre une excellente traction dans n'importe quelles conditions atmosphériques, ainsi que de très bonnes propriétés d'auto-nettoyage. Ce pneu assure aussi une expérience de conduite confortable même qu'un cycle de vie plus long.

### UM

International Standard

### Construction

BIAS

### Machinery

Agriculture: Outillage agricole, Chargeuse télescopique  
Industriel: Chargeuse télescopique, Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	14.5 - 20

### Dimensions International Standard

Ply Rating	14
Section Width (mm)	360
Overall Diameter (mm)	1116
Static Loaded Radius (mm)	495
Rolling Circumference (mm)	3315
Rim Rec	11
Rim Alt	12 SDC
ECE	E4-54R-0022638

### Load capacity (Kg)

km/h / bar	
90	2430
40	2790

*All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*