

AGRIMAX RT 855 - Spécifications techniques



Description

AGRIMAX RT 855 est un pneu caractérisé par une excellente traction et un grand confort. Il est conçu essentiellement pour le travail de la terre et les déplacements tant dans les champs que sur la route; certaines tailles sont également adaptées pour les applications de pulvérisation et le vendange. AGRIMAX RT 855 possède des excellentes qualités d'auto-nettoyage qui permettent de passer rapidement du travail aux champs aux déplacements sur route.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Pulvérisateur , Tracteur , Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	280/85 R 28 (11.2 R 28)
LI/SS	118 A8/B

Dimensions International Standard

Section Width (mm)	292
Overall Diameter (mm)	1187
Static Loaded Radius (mm)	545
Rolling Circumference (mm)	3558
Rim Rec	W 10
Rim Alt	W 9
ECE	E4-106R-000614
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	730	845	965	1085	1205	1320
40	730	845	965	1085	1205	1320
30	780	910	1035	1165	1290	1415
10 LT	975	1135	1295	1455	1615	1770
10 HT	780	910	1035	1165	1290	1415

Printed on 20/05/2021 11:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..