

AGRIMAX RT 600 - Spécifications techniques



Description

AGRIMAX RT 600 est le pneu idéal pour les pelouses et les applications récolte et pulvérisation. Grâce à sa large zone de contact, AGRIMAX RT 600 garantit une répartition optimisée de la pression sur le terrain en réduisant les dommages sur les prairies et en protégeant le sol. Grâce à la technologie avec épaule arrondie, la tringle renforcée et un nombre augmenté de crampons, ce pneu garantit une grande stabilité et une traction excellente.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Moissonneuse, Épandeur, Tracteur

Version	STANDARD
Type	TL
Tyre Size	IF680/85 R 32
LI/SS	179 D

Dimensions International Standard

Section Width (mm)	682
Overall Diameter (mm)	1960
Static Loaded Radius (mm)	846
Rolling Circumference (mm)	5860
Rim Rec	DW23 B
Rim Alt	DW21 B
ECE	E11-106R-006401

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.6	3.0
65	3645	4185	4805	5425	6045	6665	7285	7750	---	---
50	3830	4400	5050	5700	6350	7005	7655	8140	---	---
40	4010	4605	5290	5970	6650	7335	8015	8525	---	---
30	4195	4815	5530	6245	6955	7670	8385	8915	---	---
10 LT	4885	5610	6440	7270	8105	8935	9765	10385	---	---
10 HT	4195	4815	5530	6245	6955	7670	8385	8915	---	---
10 Cyc	---	---	8080	9120	10160	11205	12245	13025	12635	13175

* For 10 Cyc application Inflation pressure to be Increased by 0.8 bar.

Printed on 03/06/2021 16:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..