

## AGRIMAX RT 657 - Spécifications techniques



### Description

AGRIMAX RT 657 est le pneu idéal pour le travail aux champs et pour l'utilisation sur route; certaines tailles conviennent également pour les vendanges. Ce pneu assure un excellent confort de conduite ainsi que des économies de carburant non négligeables. Il se distingue de par une grande capacité de charge à de vitesses élevées. Agrimax RT 657 représente la meilleure solution pour ceux qui ont besoin d'un pneu polyvalent et fiable sans pour autant compromettre les performances.

### UM

International Standard

### Construction

RADIAL

### Machinery

Agriculture: Tracteur , Machine à vendanger

|           |              |
|-----------|--------------|
| Version   | STANDARD     |
| Type      | TL           |
| Tyre Size | 440/65 R 20  |
| LI/SS     | 138 D/141 A8 |

### Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Section Width (mm)         | 441            |
| Overall Diameter (mm)      | 1080           |
| Static Loaded Radius (mm)  | 479            |
| Rolling Circumference (mm) | 3240           |
| Rim Rec                    | W 14 L         |
| Rim Alt                    | W 13 ; W 15 L  |
| ECE                        | E4-106R-000760 |
| TRA Code                   | R1W            |

Load capacity (Kg)

| km/h / bar | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 1110 | 1300 | 1490 | 1655 | 1820 | 1960 | 2175 | 2360 |
| 50         | 1170 | 1365 | 1565 | 1740 | 1910 | 2060 | 2285 | 2480 |
| 40         | 1215 | 1420 | 1625 | 1805 | 1985 | 2140 | 2370 | 2575 |
| 30         | 1280 | 1495 | 1715 | 1905 | 2095 | 2255 | 2500 | 2715 |
| 10 LT      | 1490 | 1745 | 1995 | 2220 | 2440 | 2630 | 2915 | 3165 |
| 10 HT      | 1280 | 1495 | 1715 | 1905 | 2095 | 2255 | 2500 | 2715 |

Printed on 20/05/2021 09:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..