

PL 801 - Spécifications techniques



Description

PL 801 a été particulièrement conçu pour des applications avec andaineurs rotatifs/faneuses et pour les opérations de logistique avec chariots élévateurs. Ce pneu offre une excellente stabilité en même temps qu'une grande résistance à tout type de coupure. PL 801 assure un cycle de vie plus long du pneu.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Moissonneuse, Adaineur rotatif, Chariot élévateur
Industriel: Chariot élévateur

Version	STANDARD
Type	TT
Tyre Size	250 - 15 (250/70 - 15)

Dimensions International Standard

Ply Rating	20
Section Width (mm)	235
Overall Diameter (mm)	745
Rim Rec	7.50 BD
Rim Alt	7.0 ; 7.5

Load capacity (Kg)

km/h / bar	10.00
25 LOAD WHEEL	5040
25 STEER WHEEL	3875
10 OTHER VEHICLES	5040
25 OTHER VEHICLES	3875
STATIC SIDE LOADER	5850

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..