

AGRIMAX SPARGO - Spécifications techniques



Description

AGRIMAX SPARGO est le pneu BKT spécial pour les applications en couloirs, conçu pour améliorer la productivité du champ en préservant le sol à long terme. Il a d'excellentes propriétés d'auto-nettoyage et une capacité de charge supérieure à des pressions standard. AGRIMAX SPARGO garantit une excellente traction en même temps qu'une grande stabilité aux champs et lors des déplacements sur la route.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur

Version	STANDARD
Type	TL
Tyre Size	VF 320/90 R 42
LI/SS	163 D

Dimensions International Standard

Section Width (mm)	323
Overall Diameter (mm)	1642
Static Loaded Radius (mm)	764
Rolling Circumference (mm)	4995
SRI (mm)	775
Rim Rec	W 11
Rim Alt	W 10 ; DW 10 ; W 10 L ; DW 11
ECE	E11-106R-007813
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	2165	2440	2665	2800	2935	3025	3115	3270	3430	3565	3700	3815	3925	4040	4150	4330	4510
From 65 to 40	2340	2635	2880	3025	3170	3270	3365	3535	3705	3855	4000	4120	4245	4365	4485	4680	4875
30	2390	2690	2940	3085	3235	3335	3435	3610	3785	3935	4080	4205	4330	4455	4580	4780	4975
20	2435	2740	2995	3145	3300	3400	3500	3680	3855	4010	4160	4285	4415	4540	4665	4870	5070
10	2580	2900	3170	3330	3490	3595	3705	3890	4080	4240	4400	4535	4670	4805	4940	5155	5365

Printed on 23/05/2024 10:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..