

TR 126 - Spécifications techniques



Description

TR 126 a été conçu pour les micro tracteurs dans les opérations de travail de la terre. Ses revés profonds et le dessin particulier de la bande de roulement offrent d'excellentes traction et capacité de charge qui se traduisent par des performances de très haut niveau dans toutes les conditions opérationnelles.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Micro tracteur

Version	STANDARD
Type	TT
Tyre Size	6 - 14
LI/SS	66 A6

Dimensions International Standard

Ply Rating	4
Section Width (mm)	157
Overall Diameter (mm)	655
Static Loaded Radius (mm)	305
Rolling Circumference (mm)	1978
Rim Rec	5 JA ; 5 KB
ECE	E11-106R-003476
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.90
30	300

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..