

EARTHMAX SR 53 - Spécifications techniques



Description

EARTHMAX SR 53 est un pneu radial All Steel (Tout Acier) particulièrement conçu pour les chargeuses, les bulldozers et les tombereaux surbaissés (LPDT) qui opèrent dans des conditions difficiles dans des milieux rocheux y compris les opérations dans les mines souterraines et les chantiers de démolition. La bande de roulement profonde L-5 et le mélange particulièrement résistant aux coupures réduit considérablement l'usure et confère une traction et stabilité exceptionnelles.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Bulldozer, Chargeur, Tombereau surbaissé

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33
LI/SS	229 A2

Dimensions International Standard

Overall Width (mm)	910
Overall Diameter (mm)	2063
Static Loaded Radius (mm)	915
Rolling Circumference (mm)	6215
Rim Rec	28.00/3.5
Star Rating	***
TRA Code	L5

Load capacity (Kg)

km/h / bar	6.75	7.00	7.25	7.50	7.75	8.00
10	29000	30000	30750	31500	32000	32500

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..