

SAND STAR - Spécifications techniques



Description

SAND STAR est un pneu avec dessin de la bande de roulement à blocs, particulièrement conçu pour les remorques. Il assure une excellente traction sur les surfaces sableuses et un contact optimal avec le terrain, ce qui permet de réduire le compactage du sol.

UM

International Standard

Construction

BIAS

Machinery

Industriel: Remorque

Version	STANDARD
Type	TL
Tyre Size	9.00 - 13
LI/SS	119A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	245
Overall Diameter (mm)	784
Rim Rec	5.50 F
Rim Alt	5.50 WB

Load capacity (Kg)

km/h / bar	3.25
40 FR LLV	1360

Printed on 25/05/2021 10:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..