

FL 635 - Spécifications techniques



Description

FL 635 est un pneu radial Flotation adapté pour une utilisation tant sur route que dans les champs. Le dessin particulier à blocs de la bande de roulement a été conçu pour des applications de presses à balles de foin. Grâce à l'empreinte qui fournit une excellente répartition de la pression sur le terrain, le pneu FL 635 réduit nettement le compactage du sol, préservant ainsi la valeur des cultures. Le pneu assure des qualités d'autonettoyage excellentes, d'excellente durabilité et traction ainsi que des grandes propriétés de vitesse.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Presse à paille

Version	STANDARD
Type	TL
Tyre Size	650/55 R 22.5
LI/SS	167 D

Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1287
Static Loaded Radius (mm)	568
Rolling Circumference (mm)	3901
Rim Rec	AG 20.00
ECE	E4-106R-000803

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1590	1815	2035	2530	2880	3325	3770	4120	4515	4960
65	1745	1990	2235	2780	3165	3655	4145	4525	4960	5450
50	2115	2410	2705	3365	3830	4420	5015	5475	6005	6595
40	2375	2710	3045	3785	4305	4970	5640	6155	6750	7415
25	2760	3150	3535	4395	5000	5775	6550	7155	7840	8615
10	3140	3585	4025	5005	5690	6575	7460	8145	8930	9810

Printed on 02/06/2021 12:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..