

TERRA TRAX - Spécifications techniques



Description

TERRA TRAX a été spécialement conçu pour les outils de fourrage. Ce pneu est approprié tant pour une utilisation sur route que hors route. TERRA TRAX assure de bonnes performances sur route ainsi que d'excellentes qualité de confort de conduite et d'autonettoyage. La faible résistance au roulement contribue à réduire la consommation de carburant.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Outillage agricole

Version	STANDARD
Type	TL
Tyre Size	400/45L - 17.5
LI/SS	156 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	398
Overall Diameter (mm)	785
Static Loaded Radius (mm)	361
Rolling Circumference (mm)	2370
Rim Rec	14.00
ECE	E11-106R-006002

Load capacity (Kg)

km/h / bar	6.00
40	4000

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..