

EM 937 (E3) - Spécifications techniques



Description

EM 937 (E-3) a été particulièrement conçu pour les tombereaux rigides dans les applications de mines à ciel ouvert. Ce pneu offre une durabilité très élevée et une excellente résistance aux coupures et déchirures. EM 937 (E-3) est particulièrement adapté pour les opérations pénibles.

UM

International Standard

Construction

✚ BIAS

Machinery

OTR: Tombereau rigide

Version	STANDARD
Type	TL
Tyre Size	14.00 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	375
Overall Diameter (mm)	1368
Static Loaded Radius (mm)	620
Rolling Circumference (mm)	4105
Rim Rec	10.00/1.5
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	6.50	9.25
50	5600	-
10	-	10000

Printed on 23/05/2024 10:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..