

EARTHMAX SR 47 - Spécifications techniques



Description

EARTHMAX SR 47 (E-4) est un pneu radial *All Steel* (Tout Acier) particulièrement conçu pour les tombereaux rigides qui opèrent dans des conditions nécessitant la plus grande résistance aux coupures et perforations dans les milieux rocheux. Le dessin unique de la bande de roulement d'une profondeur E-4 réduit l'usure en assurant une vie plus longue du pneu même sur de longs parcours. Ceci se traduit par des temps d'arrêt machine réduits, ce qui augmente la productivité. Disponible avec mélange standard ou résistant aux coupures.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Tombereau rigide

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	195 B

Dimensions International Standard

TKPH	168
Overall Width (mm)	510
Overall Diameter (mm)	1885
Static Loaded Radius (mm)	867
Rolling Circumference (mm)	5674
Rim Rec	13.00/2.5
Star Rating	***
TRA Code	E4

Load capacity (Kg)

km/h / bar	7.25	7.50	7.75	8.00
50	11200	11500	11800	12150

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..