

RIDEMAX FL 690 - Spécifications techniques



Description

RIDEMAX FL 690 est un pneu radial Flotation et de transport bien adapté pour les camions-citernes et les remorques. Le pneu a été conçu pour les applications 75% sur route. Pour répondre à la demande pour des charges toujours plus lourdes dans l'agriculture moderne, BKT a réalisé ce pneu avec des ceintures d'acier qui confèrent une capacité de charge élevée, en augmentent la productivité de l'agriculteur. La résistance au roulement réduite contribue à l'économie de carburant.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule citerne • Remorque
Industriel: Remorque

Version	STANDARD
Type	TL
Tyre Size	VF 900/65 R 32 (VF35.5LR32)
LI/SS	197 D

Dimensions International Standard

Section Width (mm)	930
Overall Diameter (mm)	1986
Static Loaded Radius (mm)	838
Rolling Circumference (mm)	5878
SRI (mm)	925
Rim Rec	DW 31 B
Rim Alt	DW 30 ; TW 30
ECE	E11-106R-006917

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8
70	5030	6435	7840	8890	10295	11695
65	5530	7070	8610	9770	11310	12850
50	6470	8270	10075	11430	13235	15035
40	7130	9120	11110	12605	14595	16580
10	9065	11595	14125	16020	18550	21075

Printed on 23/05/2024 10:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..