

AGRIMAX FORCE - Spécifications techniques



Description

AGRIMAX FORCE, le produit phare de BKT, est un pneu radial spécialement conçu pour les applications de traitement du terrain, de transport et de récolte avec des tracteurs de grande puissance, auxquels il assure un maximum de performances et d'efficacité. Conçu avec la technologie IF, ce pneu supporte des charges lourdes avec de pressions de gonflage plus basses par rapport à un pneu standard. AGRIMAX FORCE se distingue de par une tringle renforcée en assurant une traction excellente, des excellentes qualités d'autonettoyage, une consommation réduite de carburant ainsi qu'une expérience confortable de conduite.;

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Moissonneuse, Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	IF710/55 R 34 CFO
LI/SS	170 D

Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	1646
Static Loaded Radius (mm)	746
Rolling Circumference (mm)	4962
Rim Rec	DW 25 B
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
70	2125	2455	2780	3165	3490	3875	4310	4640	5075	5460
from 65 to 40	2340	2700	3060	3480	3840	4260	4740	5100	5580	6000
30	2430	2805	3180	3615	3990	4430	4925	5300	5800	6240
20	2525	2915	3300	3755	4145	4600	5115	5505	6025	6480
10	2970	3425	3885	4415	4875	5410	6015	6475	7085	7620
Upto 30 Cyc*	3040	3510	3975	4520	4990	5535	6160	6630	7250	7800
Upto 15 Cyc*	3625	4185	4740	5390	5950	6600	7345	7905	8645	9300
10 HT	2430	2805	3180	3615	3990	4430	4925	5300	5800	6250

* - For 30 & 15 Cyc application inflation pressure to be increased by 0.8 bar.

Printed on 02/06/2021 09:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..