

AGRIMAX RT 855 - Spécifications techniques



Description

AGRIMAX RT 855 est un pneu caractérisé par une excellente traction et un grand confort. Il est conçu essentiellement pour le travail de la terre et les déplacements tant dans les champs que sur la route; certaines tailles sont également adaptées pour les applications de pulvérisation et le vendange. AGRIMAX RT 855 possède des excellentes qualités d'auto-nettoyage qui permettent de passer rapidement du travail aux champs aux déplacements sur route.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Pulvérisateur , Tracteur , Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	480/80 R 46 (18.4 R 46)
LI/SS	164 A8/B

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1936
Static Loaded Radius (mm)	895
Rolling Circumference (mm)	5871
Rim Rec	DW 16 A ; W 16 A ; DD 16
Rim Alt	W 16 L ; DD 16 L ; DW 16 L
ECE	E4-106R-000798
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	2295	2635	2975	3315	3655	3955	4250	4650	5000
40	2295	2635	2975	3315	3655	3955	4250	4650	5000
30	2460	2825	3185	3550	3915	4235	4550	4975	5350
10 LT	3080	3535	3990	4445	4900	5300	5695	6230	6700
10 HT	2460	2825	3185	3550	3915	4235	4550	4975	5350

Printed on 20/05/2021 11:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..