

SL 441 - Spécifications techniques



Description

SL 441 est un pneu adapté pour le travail de la terre et les opérations de transport avec remorques et outils agricoles. SL 441 a été conçu pour offrir une capacité de charge élevée et un long cycle de vie.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Outillage agricole, Remorque

Version	STANDARD
Type	TT
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	106 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	210
Overall Diameter (mm)	610
Static Loaded Radius (mm)	278
Rolling Circumference (mm)	1785
Rim Rec	6.75
Rim Alt	4.50 E ; 5.50 F

Load capacity (Kg)

km/h / bar	
10 FR	1330
25 FR	1130
30 FR	1065
40 FR	950

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..