

LIFTMAX LM 81 - Spécifications techniques



Description

LIFTMAX LM 81 est le pneu idéal pour les chariots élévateurs dans les applications de manutention de matériaux et industrielles. Ce pneu radial All Steel (Tout Acier) offre moins de vibrations, une stabilité supérieure ainsi que une durabilité accrue. Le mélange spécial antistatique assure une excellente résistance à l'abrasion même dans les conditions pénibles.

UM

International Standard

Construction

RADIAL

Machinery

Industriel: Chariot élévateur

Version	STANDARD
Type	TT
Tyre Size	12.00 R 24
LI/SS	178 A5

Dimensions International Standard

Overall Width (mm)	310
Overall Diameter (mm)	1235
Rim Rec	8.50
Rim Alt	9.0

Load capacity (Kg)

km/h / bar	10.00
25	7500

Printed on 02/06/2021 13:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..