

Technical Data Sheet

SIZE : VF600/65R34 AGRIMAX V-FLECTO NRO E 169D

Tire Size	VF600/65R34
Conversion Size	---
Pattern	AGRIMAX V-FLECTO
Version	STANDARD
PR	---
Star Rating	---
LI/SS	169 D
TT/TL	TL
ECE Approval No	E11-106R-007603
Tire Segment	AGRICULTURE
TRA Code	---
Rec Rim Width	DW 21 B
Alt. Rim Width	DW 20 B
SW (mm) $\pm 2\%$	597
O.D (mm) $\pm 2\%$	1644
SLR (mm) $\pm 2\%$	731
RC (mm) $\pm 2.5\%$	4952
NSD (mm) ± 1	54
No. of Lugs	22
TKPH	---
Wt. (kgs) $\pm 3\%$	201.410
Tube	---
Tube Valve	---
Flap	---



Application	Tractor
-------------	---------

Infl. Pressure (bar)	0.6	0.8	1.0	1.2	1.4	1.8	2.0	2.4
Speed (kmph)	Load capacity (kg/tyre)							
70	2430	2800	3220	3590	4010	4380	4910	5275
From 65 to 40	2670	3075	3540	3945	4410	4815	5395	5800
30	2725	3135	3610	4025	4500	4910	5505	5915
20	2775	3200	3680	4105	4585	5005	5610	6030
10	2935	3385	3895	4340	4850	5300	5935	6380
10 Cyc	3965	4565	5255	5855	6545	7150	8010	8610
10 HT	2725	3135	3610	4025	4500	4910	5505	5915

* - For 10 Cyc application inflation pressure to be increased by 0.8 bar.

Note: All Dimensions conform to ETRTO Standards

Prepared by :-
Prashant Kadam



Approved by:-
Shekhar yadav

