

Technical Data Sheet

Size: 480/70R34 AGRIMAX FACTOR E 149D/152A8

Tire Size	480/70 R 34
Conversion Size	---
Pattern	AGRIMAXFACTOR
Version	STANDARD
PR	---
Star Rating	---
LI/SS	149D / 152A8
TT/TL	TL
ECE Approval No	E11-106R-007642
Tire Segment	AGRICULTURE
TRA Code	---
Rec Rim Width	W 15 L
Alt. Rim Width	W 14 L ; W 16 L
SW (mm) $\pm$ 2%	479
O.D (mm) $\pm$ 2%	1580
SLR (mm) $\pm$ 2%	723
RC (mm) $\pm$ 2.5%	4748
NSD (mm) $\pm$ 1	49
No. of Lugs	23
TKPH	---
Wt. (kgs) $\pm$ 3%	132.490
Tube	---
Tube Valve	---
Flap	---



Application	Tractor
-------------	---------

Infl.Pressure (bar)	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
Speed (kmph)	Load capacity (kg/tyre)							
65	1530	1755	2015	2275	2535	2795	3055	3250
50	1610	1845	2120	2395	2665	2940	3215	3415
40	1675	1925	2210	2495	2780	3065	3350	3560
30	1760	2020	2320	2620	2920	3220	3520	3740
10 LT	2050	2355	2705	3050	3400	3750	4095	4355
10 HT	1760	2020	2320	2620	2920	3220	3520	3740

Note: All Dimensions conform to ETRTO Standards

Prepared by :
Prashant Kadam



Approved by :
Mr.Shekhar Yadav

