

MULTIMAX MP 513 - Spécifications techniques



Description

MULTIMAX MP 513 a été conçu par BKT pour les véhicules polyvalents dans le cadre des services municipaux de voirie et de transport pour les applications agricoles et industrielles. Grâce à sa carcasse robuste en nylon renforcée avec des ceintures d'acier, MULTIMAX MP 513 permet de transporter des charges lourdes à de grandes vitesses en assurant une expérience de conduite confortable. Il garantit une vie opérationnelle plus longue, une traction excellente ainsi que des propriétés d'autonettoyage exceptionnelles. Il est idéal pour les véhicules universels et les camions d'engrais.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Véhicule universel, Camion d'engrais
Industriel: Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	425/55 R 17 MPT
LI/SS	134 G

Dimensions International Standard

Section Width (mm)	421
Overall Diameter (mm)	900
Static Loaded Radius (mm)	399
Rolling Circumference (mm)	2695
Rim Rec	13
Rim Alt	13.00
ECE	E4-54R-0024098

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5
90	1080	1280	1550	1830	2120
65	1175	1390	1685	1990	2305
40	1245	1475	1785	2105	2440

Printed on 01/06/2021 14:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..