

Technical Data Sheet

Size: 420/70R24 AGRIMAX FACTOR E 134D/137A8

Tire Size	420/70 R 24
Conversion Size	---
Pattern	AGRIMAXFACTOR
Version	STANDARD
PR	---
Star Rating	---
LI/SS	134D / 137A8
TT/TL	TL
ECE Approval No	E11-106R-007641
Tire Segment	AGRICULTURE
TRA Code	---
Rec Rim Width	W 13
Alt. Rim Width	W 12 ; W 14 L
SW (mm) $\pm$ 2%	418
O.D (mm) $\pm$ 2%	1248
SLR (mm) $\pm$ 2%	---
RC (mm) $\pm$ 2.5%	---
NSD (mm) $\pm$ 1	43
No. of Lugs	20
TKPH	---
Wt. (kgs) $\pm$ 3%	80.800
Tube	---
Tube Valve	---
Flap	---



Application	Tractor
-------------	---------

Infl.Pressure (bar)	0.6	0.8	1.0	1.2	1.4	1.6	2.0
Speed (kmph)	Load capacity (kg/tyre)						
65	1060	1230	1400	1590	1760	1930	2120
50	1115	1295	1475	1675	1855	2030	2230
40	1165	1350	1535	1745	1930	2120	2325
30	1220	1420	1615	1830	2030	2225	2440
10 LT	1425	1655	1880	2135	2365	2590	2745
10 HT	1220	1420	1615	1830	2030	2225	2440

Note: All Dimensions conform to ETRTO Standards

Prepared by :
Prashant Kadam



Approved by :
Mr.Shekhar Yadav

