

RIDEMAX FL 699 - Spécifications techniques



Description

RIDEMAX FL 699 est le pneu BKT idéal pour les applications sur route avec remorques et camions-citernes. Ce pneu All Steel se distingue de par le kilométrage élevé et la durabilité. La tringle renforcée garantit une meilleure stabilité même à des vitesses élevées. Même si ce pneu radial a été conçu pour une utilisation sur route à 90%, c'est-à-dire pour le transport dans les applications agricoles, le nouveau RIDEMAX FL 699 offre aussi d'excellentes performances aux champs. Lors de la conception du pneu, une attention particulière a été accordée à la capacité de charge afin de réduire le nombre de cycles de transport. Bonne nouvelle aussi pour les agriculteurs qui savent combien une remorque peut compromettre la conduite : RIDEMAX FL 699 offre un confort extraordinaire en assurant une conduite sûre et un bon contrôle du véhicule.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	24 R 20.5
LI/SS	176 F

Dimensions International Standard

Ply Rating	16
Overall Width (mm)	590
Overall Diameter (mm)	1370
Static Loaded Radius (mm)	613
Rolling Circumference (mm)	4165
Rim Rec	18.00
ECE	E11-54R-0017755

Load capacity (Kg)

km/h / bar	4.0	5.0	6.0
40-50	5400	6450	7460
60-80	5140	6140	7100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/08/2025 11:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..