

## TF 8181 - Spécifications techniques



### Description

TF 8181 est un pneu pour une utilisation aux champs et sur route conçu pour les tracteurs 2WD/2RM dans les applications de travail de la terre et de transport. Ce pneu assure un excellent niveau de braquage.

### UM

International Standard

### Construction

BIAS

### Machinery

Agriculture: Tracteur 2WD  
Industriel: Remorque

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 7.50 - 18 |
| LI/SS     | 106 A6    |

### Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Ply Rating                 | 8              |
| Section Width (mm)         | 208            |
| Overall Diameter (mm)      | 875            |
| Static Loaded Radius (mm)  | 410            |
| Rolling Circumference (mm) | 2605           |
| Rim Rec                    | 5.50 F         |
| ECE                        | E4-106R-002645 |
| TRA Code                   | F2             |

### Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 3.70 |
| 30         | 950  |

publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..