

TR 145 - Spécifications techniques



Description

TR 145 a été spécialement conçu pour les tracteurs de petite taille. Le dessin particulier de la bande de roulement offre d'excellentes traction et capacité d'auto-nettoyage. Le dessin large et profond des pavés assure une plus longue vie du pneu. TR 145 bénéficie d'une zone de contact large qui lui confère un confort de conduit extraordinaire et une stabilité directionnelle élevée.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Micro tracteur

Version	STANDARD
Type	TT
Tyre Size	160/90 - 12
LI/SS	76 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	160
Overall Diameter (mm)	631
Static Loaded Radius (mm)	294
Rolling Circumference (mm)	1969
Rim Rec	4.00
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.50
30	400

its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..