

AW 705 - Spécifications techniques



Description

AW 705 a été conçu pour les outils agricoles et remorques dans les applications de travail de la terre et de transport. Il convient pour être utilisé dans l'agriculture moderne grâce à une durabilité supérieure et une capacité de charge élevée.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Presse à paille, Outillage agricole, Remorque

Version	STANDARD
Type	TL
Tyre Size	14.0/65 - 16
LI/SS FREE ROLLING	142 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	353
Overall Diameter (mm)	870
Static Loaded Radius (mm)	388
Rolling Circumference (mm)	2549
Rim Rec	11.0
ECE	E4-106R-001901

Load capacity (Kg)

km/h / bar	
10 FR	3710
25 FR	3155
30 FR	2970
40 FR	2650

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..