

FL 630 SUPER - Spécifications techniques



Description

FL 630 SUPER est un pneu Flotation particulièrement adapté pour les applications aux champs et sur route avec des remorques, camions-citernes et épandeurs. Sa structure résistante fournit une excellente traction et une adhérence parfaite même dans les virages et lors des manœuvres. Le dessin particulier de la bande de roulement garantit des propriétés de flottaison élevées en minimisant le compactage du sol en plus de propriétés d'autonettoyage exceptionnelles. FL 630 SUPER supporte des vitesses jusqu'à 70 km/h.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Épandeur, Véhicule citerne, Remorque

Version	STANDARD
Type	TL
Tyre Size	750/60 R 30.5
LI/SS	181 D

Dimensions International Standard

Section Width (mm)	754
Overall Diameter (mm)	1675
Static Loaded Radius (mm)	746
Rolling Circumference (mm)	5115
Rim Rec	AG 24.00
ECE	E4-106R-001499

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2405	2780	3155	3835	4435	5110	5785	6235	6910	7510
65	2640	3055	3465	4210	4870	5610	6355	6850	7590	8250
50	3200	3700	4195	5095	5895	6790	7690	8290	9190	9985
40	3595	4155	4715	5725	6620	7630	8640	9315	10325	11220
25	4175	4825	5475	6650	7695	8865	10040	10820	11995	13035
10	4755	5500	6240	7575	8765	10100	11435	12330	13665	14850

Printed on 01/06/2021 16:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..