

## FL 639 - Spécifications techniques



### Description

FL 639 est un pneu radial Flotation et de transport pour une utilisation essentiellement aux champs qui convient tout particulièrement pour les applications avec épandeurs. L'empreinte large garantit un moindre compactage du sol, ce qui permet une plus grande productivité des cultures. La bande de roulement renforcée et la protection du flanc contribuent à en allonger le cycle de vie. FL 639 assure une traction excellente même que des propriétés exceptionnelles d'autonettoyage.

### UM

International Standard

### Construction

RADIAL

### Machinery

Agriculture: Épandeur

|           |               |
|-----------|---------------|
| Version   | STANDARD      |
| Type      | TL            |
| Tyre Size | 560/45 R 22.5 |
| LI/SS     | 152 D/163 A8  |

### Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Section Width (mm)         | 543            |
| Overall Diameter (mm)      | 1076           |
| Static Loaded Radius (mm)  | 484            |
| Rolling Circumference (mm) | 3303           |
| Rim Rec                    | AG 16.00       |
| ECE                        | E4-106R-000627 |

Load capacity (Kg)

| km/h / bar | 0.8  | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70         | 1040 | 1200 | 1360 | 1620 | 1910 | 2170 | 2430 | 2720 | 2980 | 3235 |
| 65         | 1140 | 1320 | 1495 | 1790 | 2095 | 2380 | 2700 | 2960 | 3270 | 3550 |
| 50         | 1380 | 1595 | 1810 | 2150 | 2540 | 2900 | 3240 | 3615 | 3960 | 4300 |
| 40         | 1560 | 1805 | 2050 | 2450 | 2880 | 3270 | 3675 | 4090 | 4485 | 4875 |
| 25         | 1800 | 2080 | 2360 | 2820 | 3310 | 3775 | 4230 | 4700 | 5165 | 5610 |
| 10         | 2045 | 2365 | 2685 | 3200 | 3775 | 4300 | 4820 | 5350 | 5880 | 6390 |

Printed on 02/06/2021 11:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..