APPLICATION

The Carol R Pro 12 and Carol R Pro 20 winches meet the requirements of rescue and lifting winches. In both configurations, they can lift a maximum working load of 150 kg.
Carol R Pro winches can also be used as rope-suspension work equipment if they are equipped with a fall-arrest system complying with standard EN 363. (NB: for this configuration, the user must comply with the local regulations.



Carol R Pro 12



Carol R Pro 20

TECHNICAL CHARACTERISTICS

Carol R Pro winches are supplied with wire rope. They must be fixed to Tractel Tracpode Pro anchoring brackets.
The Carol R Pro 12 winch is fitted with a 5 mm diameter, 12 m long.
The CaRol R Pro 20 winch is fitted with a 5 mm diameter rope, 20 m long.
They have the following technical characteristics:

- Ratchet brake
- Strong steel painted frame and drum
- A protective cover protects users and mechanical components.
- Rope attachment on drum with triple safety winding.
- The winch crank can be removed to prevent use.

APPLICABLE STANDARDS

- EN1496 type A - 150 kg
- Machine Directive 2006/42/CEE

CODE

Code	Description	Weight (without pakaging	Size (without pakaging)
218438	Carol R Pro 12	5.3 kg	190 x 156 x 160 mm
218458	Carol R Pro 20	10.3 kg	245 x 200 x 190 mm

LOGISTICS INFORMATIONS

Code	Description	Code EAN	Weight (incl. pakaging)	Size (with pakaging)
218438	Carol R Pro 12	3600232184386	5.5 kg	160 x 160 x 220 mm
218458	Carol R Pro 20	3600232184584	10.8 kg	350 x 200 x 300 mm

CaRol R Pro

Treuil de levage de charge et de sauvetage

Réf. : T2648/FR
Révision : 02
Date : 01/2024

APPLICATION

Les treuils Carol R Pro 12 et Carol R Pro 20 répondent aux exigences des treuils de sauvetage et levage. Ils peuvent dans les deux configurations lever une charge maximale d'utilisation de 150 kg.
Les treuils Carol R Pro peuvent être également utilisés comme dispositifs de travail en suspension sur corde s'ils sont doublés d'un système antichute conforme à la norme EN 363. (NB : pour cette configuration l'utilisateur doit se conformer aux exigences législatives applicables sur le territoire d'utilisation.)



Carol R Pro 12



Carol R Pro 20

CARACTERISTIQUES TECHNIQUES

Les treuils Carol R Pro sont livrés avec leur câble équipé. Ils doivent être fixés sur des consoles d'ancrage Tracpode Pro de fabrication Tractel.
Le treuil Carol R Pro 12 est équipé d'un câble de diamètre 5 mm et de longueur 12 m.
Le treuil CaRol R Pro 20 est équipé d'un câble de diamètre 5 mm et de longueur 20 m.
Ils présentent les caractéristiques techniques suivantes :

- Frein à cliquet
- Châssis et tambour tôle d'acier peint de forte épaisseur
- Protection des utilisateurs et des organes mécaniques par un capot de protection.
- Attache du câble sur le tambour avec triple enroulement de sécurité
- Possibilité d'enlever la manivelle du treuil pour en condamner l'utilisation

NORMES APPLICABLES

- EN1496 type A - 150 kg
- Directive machine 2006/42/CEE

PRODUITS STANDARDS

Code	Description	Poids	Dimensions
218438	Carol R Pro 12	5.3 kg	190 x 156 x 160 mm
218458	Carol R Pro 20	10.3 kg	245 x 200 x 190 mm

INFORMATIONS LOGISTIQUES

Code	Description	Code EAN	Poids (incl. emballage)	Dimensions emballage
218438	Carol R Pro 12	3600232184386	5.5 kg	160 x 160 x 220 mm
218458	Carol R Pro 20	3600232184584	10.8 kg	350 x 200 x 300 mm