

RM 500 - Spécifications techniques



Description

RM 500 est un pneu radial avec ceintures d'acier, adapté pour les applications de récolte avec outillage agricole. Le pneu est équipé d'une carcasse robuste et un dessin particulier de la bande de roulement qui offrent une capacité de charge élevée en même temps qu'une excellente résistance aux coupures et lacérations. Grâce à son empreinte large, RM 500 assure une excellente répartition de la pression sur le terrain avec un compactage réduit du sol, en plus d'une traction exceptionnelle.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Moissonneuse

Version	STEEL BELTED
Type	TL
Tyre Size	500/85 R 30
LI/SS	176A8/164A8
LI/SS DRIVE WHEEL	164 A8
LI/SS FREE ROLLING	176 A8

Dimensions International Standard

Section Width (mm)	535
Overall Diameter (mm)	1610
Static Loaded Radius (mm)	674
Rolling Circumference (mm)	4745
Rim Rec	W 16 L
Rim Alt	W 15 L

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8
40 FR	2985	3410	3835	4690	5400	6250	7100
40 DW	2100	2400	2700	3300	3800	4400	5000

Printed on 01/06/2021 11:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..