

## AGRIMAX RT 945 - Spécifications techniques



### Description

AGRIMAX RT 945 a été conçu tout particulièrement pour les cultures en couloir : il n'abîme pas les cultures et il protège les récoltes. Qui plus est, ses capacités exceptionnelles d'auto-nettoyage permettent de passer rapidement du travail aux champs à une utilisation sur route, sur laquelle AGRIMAX RT 945 fait preuve d'une efficacité surprenante. La carcasse robuste assure une grande stabilité, une traction excellente et une durabilité extraordinaire.

### UM

International Standard

### Construction

RADIAL

### Machinery

Agriculture: Pulvérisateur , Tracteur

|           |             |
|-----------|-------------|
| Version   | STANDARD    |
| Type      | TL          |
| Tyre Size | 420/90 R 30 |
| LI/SS     | 147 A8/B    |

### Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 418             |
| Overall Diameter (mm)      | 1518            |
| Static Loaded Radius (mm)  | 684             |
| Rolling Circumference (mm) | 4571            |
| SRI (mm)                   | 725             |
| Rim Rec                    | DW13            |
| Rim Alt                    | W 14 L          |
| ECE                        | E11-106R-006021 |
| TRA Code                   | R1W             |

Load capacity (Kg)

| km/h / bar | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|
| 50         | 1665 | 2155 | 2645 | 2895 | 3075 |
| 40         | 1665 | 2155 | 2645 | 2895 | 3075 |
| 30         | 1780 | 2310 | 2835 | 3100 | 3295 |
| 10         | 2495 | 3235 | 3970 | 4340 | 4615 |

Printed on 12/12/2022 15:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..