

EARTHMAX SR 31 - Spécifications techniques



Description

EARTHMAX SR 31 est un pneu All Steel radial particulièrement conçu pour les tombereaux rigides et les chargeuses sur pneus. Les ceintures en acier multicouche assurent une force et une stabilité extraordinaires, tandis que le dessin non-directionnel rigide à blocs garantit d'excellentes traction et manœuvrabilité, même sur terrain boueux. EARTHMAX SR 31 se distingue non seulement par un confort de conduite exceptionnel, mais également par un mélange spécial de la bande de roulement, particulièrement résistante aux coupures et à la chaleur. La structure radiale de la carcasse offre de plus une faible résistance au roulement, et donc des économies de carburant non négligeables.

UM

International Standard

Construction

RADIAL

Machinery

Industriel: Bulldozer, Chargeur
OTR: Tombereau articulé, Bulldozer, Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B/208 A2

Dimensions International Standard

TKPH	270
Overall Width (mm)	765
Overall Diameter (mm)	1861
Static Loaded Radius (mm)	818
Rolling Circumference (mm)	5555
Rim Rec	25.00/3.5
Rim Alt	25.00/3.5 IF
Star Rating	**/*
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	11500	11800	12500	12850	13600	14000
10	15500	16000	17000	17500	18000	--

Printed on 02/06/2021 14:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..