

TRAC MASTER - Spécifications techniques



Description

TRAC MASTER est un pneu pour le travail de la terre et les applications pour prés et jardinage, adapté pour les micro tracteurs et les outils agricoles. Il a été conçu pour assurer la protection des champs ainsi qu'une excellente traction et des qualités extraordinaires de autonettoyage.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Outillage agricole, Micro tracteur

Version	STANDARD
Type	TL
Tyre Size	33 X 15.50 - 15

Dimensions International Standard

Ply Rating	6
Section Width (mm)	404
Overall Diameter (mm)	865
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2526
Rim Rec	13 LB
ECE	E4-106R-002329

Load capacity (Kg)

km/h / bar	2.10
50	1370

Printed on 01/06/2021 16:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..

