

## AGRIMAX RT 765 - Spécifications techniques



### Description

AGRIMAX RT 765, un pneu de la série 70 de BKT, est idéal pour équiper les tracteurs les plus modernes utilisés dans les applications lourdes, telles que traitements de terrains, déplacements aux champs et sur route, vendange et pulvérisations. La large zone de contact garantit une traction et un confort optimaux sur toutes les surfaces et à tout moment. Le pneu se distingue de par ses excellentes qualités d'autonettoyage et le compactage du sol réduit. Deux tailles sont disponibles avec la technologie de ceintures en acier.

### UM

International Standard

### Construction

RADIAL

### Machinery

Agriculture: Pulvérisateur , Tracteur , Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	620/70 R 46
LI/SS	162 D

### Dimensions International Standard

TKPH	1
Section Width (mm)	625
Overall Diameter (mm)	2036
Static Loaded Radius (mm)	924
Rolling Circumference (mm)	6106
Rim Rec	DW 20 B
ECE	E11-106R-005999
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	2615	3040	3470	3895	4325	4750
50	2745	3195	3645	4095	4545	4990
40	2865	3335	3800	4270	4740	5205
30	3010	3500	3990	4485	4975	5465
10 LT	3505	4075	4650	5220	5795	6365
10 HT	3010	3500	3990	4485	4975	5465

Printed on 20/05/2021 10:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..