

## AGRIMAX RT 955 - Spécifications techniques



### Description

AGRIMAX RT 955 est un pneu radial BKT idéal pour les applications cultures en couloir, et certaines tailles conviennent même pour la pulvérisation et les vignes. Avec son épaule arrondie, la bande de roulement assure d'excellentes performances en matière de traction, stabilité et qualités d'autonettoyage. Grâce à sa carcasse robuste, AGRIMAX RT 955 garantit une capacité de charge élevée.

### UM

International Standard

### Construction

RADIAL

### Machinery

Agriculture: Pulvérisateur , Machine à vendanger

|           |                           |
|-----------|---------------------------|
| Version   | STANDARD                  |
| Type      | TL                        |
| Tyre Size | 230/95 R 36<br>(9.5 R 36) |
| LI/SS     | 130 A8/B                  |

### Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Section Width (mm)         | 238            |
| Overall Diameter (mm)      | 1352           |
| Static Loaded Radius (mm)  | 639            |
| Rolling Circumference (mm) | 4112           |
| Rim Rec                    | W 8            |
| Rim Alt                    | W 7            |
| ECE                        | E4-106R-000765 |
| TRA Code                   | R1             |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 4.4  |
|------------|-----|------|------|------|------|------|------|------|------|------|
| 50         | 745 | 970  | 1180 | 1295 | 1370 | 1505 | 1635 | 1770 | 1900 | -    |
| 40         | 745 | 970  | 1180 | 1295 | 1370 | 1505 | 1635 | 1770 | 1900 | -    |
| 30         | 795 | 1040 | 1265 | 1385 | 1470 | 1610 | 1755 | 1895 | 2035 | -    |
| 10         | 885 | 1115 | 1370 | 1625 | 1885 | 1940 | 2170 | 2395 | 2625 | 2850 |

Printed on 20/05/2021 12:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..