

## AW 705 - Spécifications techniques



### Description

AW 705 a été conçu pour les outils agricoles et remorques dans les applications de travail de la terre et de transport. Il convient pour être utilisé dans l'agriculture moderne grâce à une durabilité supérieure et une capacité de charge élevée.

### UM

International Standard

### Construction

BIAS

### Machinery

Agriculture: Presse à paille, Outillage agricole, Remorque

|                    |              |
|--------------------|--------------|
| Version            | STANDARD     |
| Type               | TL           |
| Tyre Size          | 15.0/70 - 18 |
| LI/SS FREE ROLLING | 151 A8       |

### Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Ply Rating                 | 16             |
| Section Width (mm)         | 405            |
| Overall Diameter (mm)      | 1010           |
| Static Loaded Radius (mm)  | 447            |
| Rolling Circumference (mm) | 3092           |
| Rim Rec                    | 13.00          |
| Rim Alt                    | 13 ; W 13      |
| ECE                        | E4-106R-002266 |

### Load capacity (Kg)

| km/h / bar |      |
|------------|------|
| 10 FR      | 4830 |
| 25 FR      | 4105 |
| 30 FR      | 3865 |
| 40 FR      | 3450 |

*All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*