

FORESTECH - Spécifications techniques



Description

FORESTECH est un pneu BKT avec ceintures d'acier, adapté pour les applications en forêt avec porteurs forestiers. Ce pneu offre une excellente traction même dans des conditions de service pénibles. La tringle robuste et la zone de l'épaule renforcée assurent une grande résistance aux perforations et une vie plus longue du pneu. Par conséquent, vous pourrez réaliser sans problèmes les opérations les plus exigeantes et difficiles dans la forêt.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Porteur

Version	STEEL BELTED
Type	TL
Tyre Size	600/55 - 26.5
LI/SS	165 A8/172 A2

Dimensions International Standard

Ply Rating	20
Section Width (mm)	610
Overall Diameter (mm)	1335
Static Loaded Radius (mm)	618
Rolling Circumference (mm)	4032
Rim Rec	AG 20.00
ECE	E11-106R-003419
TRA Code	LS2

Load capacity (Kg)

km/h / bar	5.00
40	5150
30	5510
10	6300

Printed on 01/06/2021 16:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..