

RIDEMAX FL 693 M - Spécifications techniques



Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Véhicule citerne, Remorque

Version	STEEL BELTED
Type	TL
Tyre Size	VF 400/45 R 17.5
LI/SS	159 D

Dimensions International Standard

Section Width (mm)	400
Overall Diameter (mm)	800
Static Loaded Radius (mm)	343
Rolling Circumference (mm)	2357
Rim Rec	14.00
ECE	E11-106R-006068

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
70	1000	1280	1595	1795	2075	2355	2595	2830	3110	3510	3985
65	1095	1400	1750	1970	2275	2585	2845	3110	3415	3850	4375
50	1325	1695	2120	2385	2755	3125	3445	3760	4135	4660	5295
40	1490	1905	2380	2680	3095	3515	3870	4225	4645	5240	5950
30	1655	2120	2645	2975	3440	3900	4300	4695	5160	5820	6610
25	1730	2215	2770	3115	3600	4080	4495	4910	5395	6090	6915
10	1970	2520	3150	3545	4095	4650	5120	5595	6145	6930	7875

Printed on 02/06/2021 14:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..