

AGRIMAX RT 657 - Spécifications techniques



Description

AGRIMAX RT 657 est le pneu idéal pour le travail aux champs et pour l'utilisation sur route; certaines tailles conviennent également pour les vendanges. Ce pneu assure un excellent confort de conduite ainsi que des économies de carburant non négligeables. Il se distingue de par une grande capacité de charge à de vitesses élevées. Agrimax RT 657 représente la meilleure solution pour ceux qui ont besoin d'un pneu polyvalent et fiable sans pour autant compromettre les performances.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Tracteur , Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	600/65 R 34
LI/SS	157 D/160 A8

Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1644
Static Loaded Radius (mm)	742
Rolling Circumference (mm)	4960
Rim Rec	DW 20 B
Rim Alt	W 18 L
ECE	E4-106R-001405
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1980	2310	2600	2890	3180	3425	3795	4125
50	2085	2430	2735	3035	3340	3600	3990	4335
40	2160	2520	2835	3150	3465	3735	4140	4500
30	2280	2660	2990	3325	3655	3940	4370	4745
10 LT	2655	3100	3485	3875	4260	4590	5090	5530
10 HT	2280	2660	2990	3325	3655	3940	4370	4745

Printed on 20/05/2021 10:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..