

XL GRIP (T) - Spécifications techniques



Description

XL GRIP (E-3) convient tout à fait pour les tombereaux automoteurs qui transportent des charges lourdes dans les applications de mine. Le mélange de la bande de roulement est conçu pour réduire au minimum les risques de coupures et perforations sur les terrains les plus difficiles. XL GRIP (E-3) offre une traction exceptionnelle, assurant ainsi un cycle de vie élevé du pneu.

UM

International Standard

Construction

✚ BIAS

Machinery

OTR: Camion à benne basculante

Version	STANDARD
Type	TL
Tyre Size	12.00 - 24

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	320
Overall Diameter (mm)	1250
Static Loaded Radius (mm)	585
Rolling Circumference (mm)	3710
Rim Rec	8.5
Rim Alt	8.0

Load capacity (Kg)

km/h / bar	7.90
80 LS/LD	3875

Printed on 03/01/2024 15:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..