

AGRIMAX RT 855 - Spécifications techniques



Description

AGRIMAX RT 855 est un pneu caractérisé par une excellente traction et un grand confort. Il est conçu essentiellement pour le travail de la terre et les déplacements tant dans les champs que sur la route; certaines tailles sont également adaptées pour les applications de pulvérisation et le vendange. AGRIMAX RT 855 possède des excellentes qualités d'auto-nettoyage qui permettent de passer rapidement du travail aux champs aux déplacements sur route.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Pulvérisateur , Tracteur , Machine à vendanger

Version	STANDARD
Type	TL
Tyre Size	420/85 R 30 (16.9 R 30)
LI/SS	140 A8/B

Dimensions International Standard

Section Width (mm)	438
Overall Diameter (mm)	1475
Static Loaded Radius (mm)	661
Rolling Circumference (mm)	4421
Rim Rec	W 15 L
Rim Alt	W 13 ; W 14 L
ECE	E4-106R-000654
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1375	1600	1825	2050	2275	2500
40	1375	1600	1825	2050	2275	2500
30	1475	1715	1955	2195	2435	2675
10 LT	1845	2145	2450	2750	3050	3350
10 HT	1475	1715	1955	2195	2435	2675

Printed on 20/05/2021 11:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..