

AGRIMAX FORCE - Spécifications techniques



Description

AGRIMAX FORCE, le produit phare de BKT, est un pneu radial spécialement conçu pour les applications de traitement du terrain, de transport et de récolte avec des tracteurs de grande puissance, auxquels il assure un maximum de performances et d'efficacité. Conçu avec la technologie IF, ce pneu supporte des charges lourdes avec de pressions de gonflage plus basses par rapport à un pneu standard. AGRIMAX FORCE se distingue de par une tringle renforcée en assurant une traction excellente, des excellentes qualités d'autonettoyage, une consommation réduite de carburant ainsi qu'une expérience confortable de conduite.;

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Moissonneuse, Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	IF620/75 R 30 CFO
LI/SS	169 D

Dimensions International Standard

Section Width (mm)	650
Overall Diameter (mm)	1703
Static Loaded Radius (mm)	759
Rolling Circumference (mm)	5100
Rim Rec	DW 23 B
Rim Alt	DW 21 B
ECE	E11-106R-006469
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2475	2845	3270	3690	4110	4535	4955	5275
From 65 to 40	2725	3130	3595	4060	4520	4985	5450	5800
30	2830	3288	3735	4220	4700	5180	5665	6030
20	2940	3380	3880	4380	4880	5380	5885	6260
10	3460	3975	4565	5155	5740	6330	6920	7365
Upto 30 Cyc*	3540	4065	4670	5275	5875	6480	7085	7540
Upto 15 Cyc*	4220	4850	5570	6290	7005	7725	8445	8990
10 HT	2830	3255	3735	4220	4700	5180	5665	6030

* - For 30 & 15 Cyc application Inflation pressure to be increased by 0.8 bar.

Printed on 02/06/2021 09:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..