

MAILLON RAPIDE - Petite ouverture

RÉF. 5190

Acier zingué ou **INOX AISI 316** / Coefficient de sécurité 1/5

CODE ZINGUÉ	AAG	ABG	AG	BG	CG	DG	EG	FG*
CODE INOX	AAI	ABI	AI	BI	CI	DI	EI	FI
CMU (kg) ZINGUÉ	35	50	100	180	280	400	550	700
CMU (kg) INOX	100	160	220	280	450	650	900	1100
D (mm)	2,5	3	3,5	4	5	6	7	8
L (mm)	21	25	29	31,5	39,5	45	52	58
H (mm)	7	8,5	10	11,5	13	14,5	16	17,5
O (ouverture) (mm)	3,5	4	5	5,5	6,5	7,5	8,5	11
Poids (kg)	0,003	0,005	0,008	0,012	0,021	0,035	0,052	0,078

CODE ZINGUÉ	GG	HG*	IG	JG	KG	LG	MG
CODE INOX	GI	HI	II	JI	KI	-	-
CMU (kg) ZINGUÉ	900	1100	1500	2200	2900	3500	4000
CMU (kg) INOX	1400	1800	2500	3500	4500	-	-
D (mm)	9	10	12	14	16	18	20
L (mm)	62	69	80,5	93	108	121	137,5
H (mm)	19	20,5	23,5	26,5	29,5	32,5	35,5
O (ouverture) (mm)	11	12	15	17	19	23	26
Poids (kg)	0,1	0,14	0,24	0,37	0,57	0,8	1,1

PETITE OUVERTURE

zingué



* HOMOLOGUÉ
EPI EN362



MAILLON RAPIDE - Grande ouverture

RÉF. 5191

Acier zingué ou **INOX AISI 316** / Coefficient de sécurité 1/5

CODE ZINGUÉ	AAG	ABG	AG	BG	CG	DG	EG*	FG*
CODE INOX	AAI	ABI	AI	BI	CI	DI	EI	FI
CMU en kg ZINGUÉ	30	45	90	160	250	350	500	650
CMU en kg INOX	90	145	200	250	400	580	800	980
D en mm	2,5	3	3,5	4	5	6	7	8
L en mm	28	33,5	39	45	52	58,5	65	72
H en mm	7	8,5	10	11,5	13	14,5	16	17,5
O (ouverture) en mm	7	8,5	10	11,5	13	14,5	16	17,5
Poids en kg	0,004	0,007	0,010	0,015	0,026	0,042	0,062	0,093

CODE ZINGUÉ	GG	HG*	IG	JG	KG	LG	MG
CODE INOX	GI	HI	II	JI	KI	-	-
CMU en kg ZINGUÉ	800	1000	1250	2000	2500	3000	3600
CMU en kg INOX	1250	1600	2200	3100	4000	-	-
D en mm	9	10	12	14	16	18	20
L en mm	77	85,5	100	114	129	140,5	158,5
H en mm	19	20,5	23,5	26,5	29,5	32,5	35,5
O (ouverture) en mm	19	20,5	23,5	26,5	29,5	32,5	35,5
Poids en kg	0,12	0,16	0,27	0,43	0,64	0,89	1,22

GRANDE OUVERTURE

zingué



* HOMOLOGUÉ
EPI EN362



MAILLON RAPIDE - Delta


RÉF. 5193

Acier zingué ou **INOX AISI 316** / Coefficient de sécurité 1/5

CODE ZINGUÉ	AG	BG	CG	DG	EG	FG*	GG
CODE INOX	AI	BI	CI	DI	EI	FI	GI
CMU en kg ZINGUÉ	70	100	150	250	400	550	700
CMU en kg INOX	150	200	325	450	625	770	980
D en mm	3,5	4	5	6	7	8	9
L en mm	29	32	38	44	49	57	60
L1 en mm	24	27,5	30	35	37	40	42
O (ouverture) en mm	5	5,5	6,5	7,5	8,5	10	11
Poids en kg (ZINGUÉ)	0,009	0,014	0,023	0,039	0,058	0,086	0,115
Poids en kg (INOX)	0,010	0,014	0,024	0,040	0,059	0,088	0,115

CODE ZINGUÉ	HG	IG	JG	KG	LG	MG
CODE INOX	HI	II	JI	KI		
CMU en kg ZINGUÉ	900	1100	1800	2200	2600	3000
CMU en kg INOX	1250	1750	2450	3150	4200	-
D en mm	10	12	14	16	18	20
L en mm	67	80	95	106	119	136
L1 en mm	46	51	57	61	66	72
O (ouverture) en mm	12	15	17	19	23	24
Poids en kg (ZINGUÉ)	0,153	0,256	0,404	0,612	0,845	1,185
Poids en kg (INOX)	0,156	0,262	0,414	0,627	0,866	-

zingué



* HOMOLOGUÉ
EPI EN362

