

MANILLE DROITE – Type commercial


RÉF. 5235

Acier zingué - Coefficient de sécurité 1/5

CODE	A	B	D	F	G	H	I
CMU (kg)	70	100	250	400	630	750	1000
diam D (mm)	5	6	8	10	12	14	16
A (mm)	10	13	16	19	25	28	32
H (mm)	19	25	32	38	51	57	64
poids (kg)	0,014	0,03	0,047	0,089	0,17	0,31	0,38

CODE	K	L	M	N	O	P	Q
CMU (kg)	1600	2000	2500	3150	4000	6000	8000
diam D (mm)	20	22	24	28	32	38	42
A (mm)	38	44	48,5	57	64	76	84
H (mm)	76	80	84	115	127	152	164
poids (kg)	0,73	1,32	2,07	2,88	3,60	6,10	7,8

TYPE COMMERCIAL



MANILLE LYRE – Type commercial

RÉF. 5255

Acier zingué - Coefficient de sécurité 1/5

CODE	A	B	D	F	G	H	I	J
CMU (kg)	80	100	200	300	500	600	800	1100
diam.D (mm)	5	6	8	10	12	14	16	18
A (mm)	10	13	16	19	25	28	32	38
C (mm)	16	20	24	32	38	44	50	56
H (mm)	19	25	32	38	51	57	64	77
poids (kg)	0,015	0,027	0,063	0,12	0,21	0,34	0,5	0,6

CODE	K	L	M	N	O	P	Q
CMU (kg)	1100	1500	2000	2600	3200	4500	6000
diam. D (mm)	20	22	24	28	32	38	42
A (mm)	38	44	48,5	57	64	76	84
C (mm)	66	74	68	94	104	136	142
H (mm)	76	80	96	115	127	152	164
poids (kg)	0,98	1,31	1,92	2,7	4,03	6,74	8

TYPE COMMERCIAL

