

MANILLE DROITE – Standard

RÉF. 5230


Acier estampé zingué

Coefficient de sécurité 1/5

CODE	AG	BG	DG	FG	GG	HG	IG	JG	KG
CMU (kg)	70	100	250	400	630	750	1000	1300	1600
d (mm)	5	6	8	10	12	14	16	18	20
C (mm)	5	6	8	10	12	14	16	18	20
E (mm)	8	11	16	19	26	28	30	28	35
H (mm)	23	29	37	41	54	57	63	62	65
poids (kg)	0,02	0,04	0,08	0,011	0,25	0,34	0,51	0,75	0,94

CODE	LG	MMG	NG	OG	PG	QG	RG	SG
CMU (kg)	2000	2500	3150	4000	5000	6300	7100	8000
d (mm)	22	25	27	30	33	36	39	42
C (mm)	21	22	27	30	33	36	39	38
E (mm)	41	36	54	60	66	72	78	60
H (mm)	75	81	89	99	103	111	126	131
poids (kg)	1,3	1,6	2	2,83	3,7	4,8	6	7,4

ESTAMPÉE



MANILLE LYRE – Standard

RÉF. 5250

Acier estampé zingué / Coefficient de sécurité 1/5

CODE	AG	BG	DG	FG	GG	HG	IG	JG
CMU (kg)	80	100	200	300	500	600	800	1250
d (mm)	5	6	8	10	12	14	16	18
C (mm)	5	6	8	10	12	15	18	18
H (mm)	20	24	31	38	53	59	64	82
E (mm)	10	12	15	16	23	30	30	35
D (mm)	16	20	24	30	39	47	48	52
poids (kg)	0,019	0,034	0,08	0,1	0,28	0,39	0,48	0,71

CODE	KG	LG	MMG	NG	OG	PG	QG	RG
CMU (kg)	1100	1500	2000	3150	4000	5000	6300	7100
d (mm)	20	22	25	27	30	33	36	39
C (mm)	19,5	22	25	27	30	33	36	39
H (mm)	72	85	100	120	118	128	143	153
E (mm)	35	46	50	54	60	66	72	78
D (mm)	59	61	81	80	89	100	106	113
poids (kg)	0,96	1,37	2,00	2,42	3,23	4,25	5,70	7,1

ESTAMPÉE

