

TALIA[®]

PLAST

A French manufacturer for your safety at work



OPUS[®]



OCÉANIC[®]II



VISIOOCÉANIC[®]II



OPALE[®]



ORIZON[®]



TALIACAP[®]

THE ONLY
FRENCH
MANUFACTURER
with
FULLY
INTEGRATED
SAFETY
HELMETS

Data sheets

Colours

	<input checked="" type="radio"/> White
	<input checked="" type="radio"/> Yellow P116C
	<input checked="" type="radio"/> Green P347C
	<input checked="" type="radio"/> Blue P2935C
	<input checked="" type="radio"/> Orange P179C
	<input checked="" type="radio"/> Red P1797C
	<input type="radio"/> Neon Yellow

Cradle

Description		
<input checked="" type="radio"/> RB	<input checked="" type="radio"/> TB	<input type="radio"/> RB
Web plastic	Textile	Monobloc plastic

Number of Anchorage points		
<input type="radio"/> 4 Pts	<input type="radio"/> 4 Pts	<input type="radio"/> 4 Pts
<input checked="" type="radio"/> 6 Pts	<input checked="" type="radio"/> 6 Pts	<input type="radio"/> 6 Pts

Standard adjustment (size 53 - 61 cm)		
<input checked="" type="radio"/> RB	<input checked="" type="radio"/> TB	<input type="radio"/> RB

Ratchet adjustment (size 53 - 61 cm)		
<input checked="" type="radio"/> RB	<input checked="" type="radio"/> TB	<input type="radio"/> RB

Components		
<input checked="" type="radio"/> PE BD	<input checked="" type="radio"/> PE BD	<input type="radio"/> PE BD
<input type="radio"/> PE MD	<input checked="" type="radio"/> PE MD	<input type="radio"/> PE MD

Sweatband		
<input type="radio"/> 20 cm	<input type="radio"/> 20 cm	<input type="radio"/> 20 cm
<input checked="" type="radio"/> 37 cm	<input checked="" type="radio"/> 37 cm	<input type="radio"/> 37 cm
<input type="radio"/> 40 cm	<input type="radio"/> 40 cm	<input type="radio"/> 40 cm

Shell material

<input checked="" type="radio"/> HDPE (High density polyethylene)
<input type="radio"/> ABS

Weight

370 g

Life expectancy

(from the date of manufacture and in normal conditions of storage and use)

<input type="radio"/> 3 years
<input checked="" type="radio"/> 5 years

Ventilated sides

<input checked="" type="radio"/> Adjustable
<input type="radio"/> Non-adjustable

Temperature resistance

<input type="radio"/> -10°C	<input checked="" type="radio"/> -20°C	<input type="radio"/> -30°C	<input checked="" type="radio"/> +50°C
-----------------------------	--	-----------------------------	--

Electrical insulation (non-vented only)
<input checked="" type="radio"/> Electrical class 0 → Alternating voltage up to 1000 V or direct voltage up to 1500 V : electrical insulation for use on low voltage installations.

Protection against molten metal splash
<input checked="" type="radio"/> MM

Adjustable accessories

<input type="radio"/> Reflective material
<input checked="" type="radio"/> Adhesive badge holder
<input type="radio"/> Detachable badge holder
<input checked="" type="radio"/> Protective ear muffs
<input checked="" type="radio"/> Headlamp
<input checked="" type="radio"/> Chin strap* 2-point (cotton, leather or textile)
<input checked="" type="radio"/> Chin strap* 4-point (textile)
<input checked="" type="radio"/> "Forester" mesh
<input checked="" type="radio"/> Protective visor
<input type="radio"/> Spare glass
<input checked="" type="radio"/> Bulb holder and grommet (not compatible with the 440 Va option)

*Special anchorage for our models



PROTECTIVE HELMET OPUS®

Data sheet - English version
Personal Protection Equipment



CE - EN 397
- EN 50365

Main applications :

- Industrial production and construction.

Product advantages :

- Traceability : date of manufacture and batch identification marked under the helmet peak.
- Excellent impact and penetration resistance.
- An accurate and easily adjustable wheel ratchet - no clutch necessary - for a perfect set up of the helmet on the head. The wheel ratchet is positioned on the neck to create a firm comfort fit with added security in the event of shocks.



Marking (e.g.: company logo)

Screen printing	
<input checked="" type="radio"/> Front	L 45 x H 40 mm
<input checked="" type="radio"/> Side	L 75 x H 15 mm
<input type="radio"/> Back	-

TALIA®
PLAST

SOFOP S.A.S taliaplast®
3 route de la Torse
44550 Montoir de Bretagne - France

Société Française d'Outils Professionnels
SAS au capital de **10 000 000 Euros**
006 780 514 R.C.S. Saint-Nazaire
SIREN 006 780 514 - APE 2229 B
N° TVA FR 72 006 780 514
Identifiant EORI : FR 006 780 514 00037

www.taliaplast.com

Export DPT

GRAND EXPORT / OVERSEAS Area
e-mail: export@taliaplast.com
Phone: +33 (0) 251 16 60 86

EUROPE / EUROPE Area
e-mail: sales@taliaplast.com
Phone: +33 (0) 251 16 61 02

Commercial France

Tél. 02 51 16 60 60
e-mail : commercialfrance@taliaplast.com

Key :

- Available in the range
- Option possible (contact us)
- Not available

Colours

	<input checked="" type="radio"/> White
	<input checked="" type="radio"/> Yellow P116C
	<input checked="" type="radio"/> Green P347C
	<input checked="" type="radio"/> Blue P2935C
	<input checked="" type="radio"/> Orange P179C
	<input checked="" type="radio"/> Red P1797C
	<input checked="" type="radio"/> Neon Yellow

Cradle

Description		
<input checked="" type="radio"/> RB	<input checked="" type="radio"/> TB	<input type="radio"/> RB
Web plastic	Textile	Monobloc plastic

Number of Anchorage points		
<input type="radio"/> 4 Pts	<input type="radio"/> 4 Pts	<input type="radio"/> 4 Pts
<input checked="" type="radio"/> 6 Pts	<input checked="" type="radio"/> 6 Pts	<input type="radio"/> 6 Pts

Standard adjustment (size 53 - 61 cm)		
<input checked="" type="radio"/> RB	<input checked="" type="radio"/> TB	<input type="radio"/> RB

Ratchet adjustment (size 53 - 61 cm)		
<input checked="" type="radio"/> RB	<input checked="" type="radio"/> TB	<input type="radio"/> RB

Components		
<input checked="" type="radio"/> PE BD	<input checked="" type="radio"/> PE BD	<input type="radio"/> PE BD
<input type="radio"/> PE MD	<input checked="" type="radio"/> PE MD	<input type="radio"/> PE MD

Sweatband		
<input type="radio"/> 20 cm	<input type="radio"/> 20 cm	<input type="radio"/> 20 cm
<input checked="" type="radio"/> 37 cm	<input checked="" type="radio"/> 37 cm	<input type="radio"/> 37 cm
<input type="radio"/> 40 cm	<input type="radio"/> 40 cm	<input type="radio"/> 40 cm

Shell material

<input checked="" type="radio"/> HDPE (High density polyethylene)
<input type="radio"/> ABS

Weight

370 g

Life expectancy

(from the date of manufacture and in normal conditions of storage and use)

<input type="radio"/> 3 years
<input checked="" type="radio"/> 5 years

Ventilated sides

<input checked="" type="radio"/> Adjustable
<input type="radio"/> Non-adjustable

Temperature resistance

<input type="radio"/> -10°C	<input type="radio"/> -20°C	<input checked="" type="radio"/> -30°C	<input checked="" type="radio"/> +50°C
-----------------------------	-----------------------------	--	--

Electrical insulation (non-vented only)	
<input checked="" type="radio"/>	Electrical class 0 → Alternating voltage up to 1000 V or direct voltage up to 1500 V : electrical insulation for use on low voltage installations.

Protection against molten metal splash	
<input checked="" type="radio"/> MM	

Adjustable accessories

<input type="radio"/> Reflective material
<input checked="" type="radio"/> Adhesive badge holder
<input type="radio"/> Detachable badge holder
<input checked="" type="radio"/> Protective ear muffs
<input checked="" type="radio"/> Headlamp
<input checked="" type="radio"/> Chin strap* 2-point (cotton, leather or textile)
<input checked="" type="radio"/> Chin strap* 4-point (textile)
<input checked="" type="radio"/> "Forester" mesh
<input checked="" type="radio"/> Protective visor
<input type="radio"/> Spare glass
<input checked="" type="radio"/> Bulb holder and grommet (not compatible with the 440 Va option)

*Special anchorage for our models



PROTECTIVE HELMET

OCÉANIC® II

Data sheet - English version
Personal Protection Equipment



CE - EN 397
- EN 50365

Main applications :

- Industrial production and construction.

Product advantages :

- Traceability : date of manufacture and batch identification marked under the helmet peak.
- Excellent impact and penetration resistance.
- An accurate and easily adjustable wheel ratchet - no clutch necessary - for a perfect set up of the helmet on the head. The wheel ratchet is positioned on the neck to create a firm comfort fit with added security in the event of shocks.



Marking (e.g.: company logo)

Screen printing	
<input checked="" type="radio"/> Front	L 60 x H 50 mm
<input checked="" type="radio"/> Side	L 75 x H 15 mm
<input checked="" type="radio"/> Back	L 25 x H 15 mm

TALIA®
PLAST

SOFOP S.A.S taliaplast®
3 route de la Torse
44550 Montoir de Bretagne - France

Société Française d'Outils Professionnels
SAS au capital de **10 000 000 Euros**
006 780 514 R.C.S. Saint-Nazaire
SIREN 006 780 514 - APE 2229 B
N° TVA FR 72 006 780 514
Identifiant EORI : FR 006 780 514 00037

www.taliaplast.com

Export DPT

GRAND EXPORT / OVERSEAS Area
e-mail: export@taliaplast.com
Phone: +33 (0) 251 16 60 86

EUROPE / EUROPE Area
e-mail: sales europe@taliaplast.com
Phone: +33 (0) 251 16 61 02

Commercial France

Tél. 02 51 16 60 60
e-mail: commercialfrance@taliaplast.com

Key :

- Available in the range
- Option possible (contact us)
- Not available

Colours

	<input checked="" type="radio"/> White
	<input checked="" type="radio"/> Yellow P116C
	<input checked="" type="radio"/> Green P347C
	<input checked="" type="radio"/> Blue P2935C
	<input checked="" type="radio"/> Orange P179C
	<input checked="" type="radio"/> Red P1797C
	<input checked="" type="radio"/> Neon Yellow

Shell material

<input checked="" type="radio"/> HDPE (High density polyethylene)
<input type="radio"/> ABS

Life expectancy

(from the date of manufacture and in normal conditions of storage and use)

<input type="radio"/> 3 years
<input checked="" type="radio"/> 5 years

Cradle

Description

<input checked="" type="radio"/> RB	<input checked="" type="radio"/> TB	<input type="radio"/> RB
Web plastic	Textile	Monobloc plastic

Number of Anchorage points

<input type="radio"/> 4 Pts	<input type="radio"/> 4 Pts	<input type="radio"/> 4 Pts
<input checked="" type="radio"/> 6 Pts	<input checked="" type="radio"/> 6 Pts	<input type="radio"/> 6 Pts

Standard adjustment (size 53 - 61 cm)

<input checked="" type="radio"/> RB	<input checked="" type="radio"/> TB	<input type="radio"/> RB
-------------------------------------	-------------------------------------	--------------------------

Ratchet adjustment (size 53 - 61 cm)

<input checked="" type="radio"/> RB	<input checked="" type="radio"/> TB	<input type="radio"/> RB
-------------------------------------	-------------------------------------	--------------------------

Components

<input checked="" type="radio"/> PE BD	<input checked="" type="radio"/> PE BD	<input type="radio"/> PE BD
<input type="radio"/> PE MD	<input checked="" type="radio"/> PE MD	<input type="radio"/> PE MD

Sweatband

<input type="radio"/> 20 cm	<input type="radio"/> 20 cm	<input type="radio"/> 20 cm
<input checked="" type="radio"/> 37 cm	<input checked="" type="radio"/> 37 cm	<input type="radio"/> 37 cm
<input type="radio"/> 40 cm	<input type="radio"/> 40 cm	<input type="radio"/> 40 cm

Weight

400 g

Ventilated sides

<input checked="" type="radio"/> Adjustable
<input type="radio"/> Non-adjustable

Temperature resistance

<input type="radio"/> -10°C	<input type="radio"/> -20°C	<input checked="" type="radio"/> -30°C	<input checked="" type="radio"/> +50°C
-----------------------------	-----------------------------	--	--

Electrical insulation (non-vented only)

<input type="radio"/> Electrical class 0 → Alternating voltage up to 1000 V or direct voltage up to 1500 V : electrical insulation for use on low voltage installations.
--

Protection against molten metal splash

<input checked="" type="radio"/> MM

Adjustable accessories

<input type="radio"/> Reflective material
<input type="radio"/> Adhesive badge holder
<input type="radio"/> Detachable badge holder
<input checked="" type="radio"/> Protective ear muffs
<input checked="" type="radio"/> Headlamp
<input checked="" type="radio"/> Chin strap* 2-point (cotton, leather or textile)
<input checked="" type="radio"/> Chin strap* 4-point (textile)
<input type="radio"/> "Forester" mesh
<input type="radio"/> Protective visor
<input checked="" type="radio"/> Spare glass
<input type="radio"/> Bulb holder and grommet (not compatible with the 440 Va option)

*Special anchorage for our models



PROTECTIVE HELMET

VISIOCÉANIC®

Data sheet - **English** version
Personal Protection Equipment



Helmet :

CE - EN 397

Polycarbonate integrated eyewear safety :

CE - EN 166

Main applications :

- Industrial production and construction.

Product advantages :

- Easily retractable clear screen for maximum eye protection.
- Traceability : date of manufacture and batch identification marked under the helmet peak.
- Excellent impact and penetration resistance.
- An accurate and easily adjustable wheel ratchet - no clutch necessary - for a perfect set up of the helmet on the head. The wheel ratchet is positioned on the neck to create a firm comfort fit with added security in the event of shocks.



Marking (e.g.: company logo)

Screen printing

<input checked="" type="radio"/> Front	L 60 x H 50 mm
<input checked="" type="radio"/> Side	L 75 x H 15 mm
<input checked="" type="radio"/> Back	L 25 x H 15 mm

Key :

- Available in the range
- Option possible (contact us)
- Not available

TALIA®
PLAST

SOFOP S.A.S taliaplast®
3 route de la Torse
44550 Montoir de Bretagne - France

Société Française d'Outils Professionnels
SAS au capital de **10 000 000 Euros**
006 780 514 R.C.S. Saint-Nazaire
SIREN 006 780 514 - APE 2229 B
N° TVA FR 72 006 780 514
Identifiant EORI : FR 006 780 514 00037

www.taliaplast.com

Export DPT

GRAND EXPORT / OVERSEAS Area
e-mail: export@taliaplast.com
Phone: +33 (0) 251 16 60 86

EUROPE / EUROPE Area
e-mail: sales@taliaplast.com
Phone: +33 (0) 251 16 61 02

Commercial France

Tél. 02 51 16 60 60
e-mail: commercialfrance@taliaplast.com

Colours

	<input checked="" type="radio"/> White
	<input checked="" type="radio"/> Yellow P116C
	<input checked="" type="radio"/> Green P347C
	<input checked="" type="radio"/> Blue P2935C
	<input checked="" type="radio"/> Orange P179C
	<input checked="" type="radio"/> Red P1797C
	<input checked="" type="radio"/> Neon Yellow

Cradle

Description

<input type="radio"/> RB Web plastic	<input type="radio"/> TB Textile	<input checked="" type="radio"/> RB Monobloc plastic
---	-------------------------------------	---

Number of Anchorage points

<input type="radio"/> 4 Pts	<input type="radio"/> 4 Pts	<input type="radio"/> 4 Pts
<input type="radio"/> 6 Pts	<input type="radio"/> 6 Pts	<input checked="" type="radio"/> 6 Pts

Standard adjustment (size 53 - 61 cm)

<input type="radio"/> RB	<input type="radio"/> TB	<input checked="" type="radio"/> RB
--------------------------	--------------------------	-------------------------------------

Ratchet adjustment (size 53 - 61 cm)

<input type="radio"/> RB	<input type="radio"/> TB	<input type="radio"/> RB
--------------------------	--------------------------	--------------------------

Components

<input type="radio"/> PE BD	<input type="radio"/> PE BD	<input checked="" type="radio"/> PE BD
<input type="radio"/> PE MD	<input type="radio"/> PE MD	<input type="radio"/> PE MD

Sweatband

<input type="radio"/> 20 cm	<input type="radio"/> 20 cm	<input checked="" type="radio"/> 20 cm
<input type="radio"/> 37 cm	<input type="radio"/> 37 cm	<input type="radio"/> 37 cm
<input type="radio"/> 40 cm	<input type="radio"/> 40 cm	<input type="radio"/> 40 cm

Shell material

<input checked="" type="radio"/> HDPE (High density polyethylene)
<input type="radio"/> ABS

Weight

340 g

Life expectancy

(from the date of manufacture and in normal conditions of storage and use)

<input type="radio"/> 3 years
<input checked="" type="radio"/> 5 years

Ventilated sides

<input type="radio"/> Adjustable
<input type="radio"/> Non-adjustable

Temperature resistance

<input checked="" type="radio"/> -10°C	<input type="radio"/> -20°C	<input type="radio"/> -30°C	<input checked="" type="radio"/> +50°C
--	-----------------------------	-----------------------------	--

Electrical insulation

<input checked="" type="radio"/> Electrical class 0 → Alternating voltage up to 1000 V or direct voltage up to 1500 V : electrical insulation for use on low voltage installations.

Protection against molten metal splash

<input type="radio"/> MM

Adjustable accessories

<input type="radio"/> Reflective material
<input type="radio"/> Adhesive badge holder
<input type="radio"/> Detachable badge holder
<input checked="" type="radio"/> Protective ear muffs
<input checked="" type="radio"/> Headlamp
<input checked="" type="radio"/> Chin strap* 2-point (cotton, leather or textile)
<input checked="" type="radio"/> Chin strap* 4-point (textile)
<input checked="" type="radio"/> "Forester" mesh
<input checked="" type="radio"/> Protective visor
<input type="radio"/> Spare glass
<input checked="" type="radio"/> Bulb holder and grommet (not compatible with the 440 Va option)

*Special anchorage for our models



PROTECTIVE HELMET

OPALE®

Data sheet - **English** version
Personal Protection Equipment



CE - EN 397
EN 50365

Main applications :

- Industrial production and construction.

Product advantages :

- Monobloc lining.
- Electrical insulation : Electrical class 0 : alternating voltage up to 1000 V or direct voltage up to 1500 V (non-vented helmet).
- Traceability: date of manufacture and batch identification marked under the helmet peak.
- Excellent impact and penetration resistance.



Marking (e.g.: company logo)

Screen printing

<input checked="" type="radio"/> Front	L 50 x H 40 mm
<input checked="" type="radio"/> Side	L 75 x H 15 mm
<input type="radio"/> Back	-

TALIA®
PLAST

SOFOP S.A.S taliaplast®
3 route de la Torse
44550 Montoir de Bretagne - France

Société Française d'Outils Professionnels
SAS au capital de **10 000 000 Euros**
006 780 514 R.C.S. Saint-Nazaire
SIREN 006 780 514 - APE 2229 B
N° TVA FR 72 006 780 514
Identifiant EORI : FR 006 780 514 00037

www.taliaplast.com

Export DPT

GRAND EXPORT / OVERSEAS Area
e-mail: export@taliaplast.com
Phone: +33 (0) 251 16 60 86

EUROPE / EUROPE Area
e-mail: sales@taliaplast.com
Phone: +33 (0) 251 16 61 02








Commercial France

Tél. 02 51 16 60 60
e-mail : commercialfrance@taliaplast.com

Key :

- Available in the range
- Option possible (contact us)
- Not available

Colours

	<input checked="" type="radio"/> White
	<input type="radio"/> Yellow P116C
	<input type="radio"/> Green P347C
	<input type="radio"/> Blue P2935C
	<input type="radio"/> Orange P179C
	<input type="radio"/> Red P1797C
	<input type="radio"/> Neon Yellow

Shell material

<input checked="" type="radio"/> HDPE (High density polyethylene)
<input type="radio"/> ABS

Life expectancy

(from the date of manufacture and in normal conditions of storage and use)

<input checked="" type="radio"/> 3 years
<input type="radio"/> 5 years

Cradle

Description

<input checked="" type="radio"/> RB	<input type="radio"/> TB	<input type="radio"/> RB
Web plastic	Textile	Monobloc plastic

Number of Anchorage points

<input checked="" type="radio"/> 4 Pts	<input checked="" type="radio"/> 4 Pts	<input type="radio"/> 4 Pts
<input type="radio"/> 6 Pts	<input type="radio"/> 6 Pts	<input type="radio"/> 6 Pts

Standard adjustment (size 53 - 61 cm)

<input checked="" type="radio"/> RB	<input checked="" type="radio"/> TB	<input type="radio"/> RB
-------------------------------------	-------------------------------------	--------------------------

Ratchet adjustment (size 53 - 61 cm)

<input type="radio"/> RB	<input type="radio"/> TB	<input type="radio"/> RB
--------------------------	--------------------------	--------------------------

Components

<input checked="" type="radio"/> PE BD	<input checked="" type="radio"/> PE BD	<input type="radio"/> PE BD
<input type="radio"/> PE MD	<input type="radio"/> PE MD	<input type="radio"/> PE MD

Sweatband

<input checked="" type="radio"/> 20 cm	<input checked="" type="radio"/> 20 cm	<input type="radio"/> 20 cm
<input type="radio"/> 37 cm	<input type="radio"/> 37 cm	<input type="radio"/> 37 cm
<input type="radio"/> 40 cm	<input type="radio"/> 40 cm	<input type="radio"/> 40 cm

Weight

205 g

Ventilated sides

<input type="radio"/> Adjustable
<input type="radio"/> Non-adjustable

Temperature resistance

<input checked="" type="radio"/> -10°C	<input type="radio"/> -20°C	<input type="radio"/> -30°C	<input checked="" type="radio"/> +50°C
--	-----------------------------	-----------------------------	--

Electrical insulation (non-vented only)

<input type="radio"/>  Electrical class 0 → Alternating voltage up to 1000 V or direct voltage up to 1500 V : electrical insulation for use on low voltage installations.
--

Protection against molten metal splash

<input type="radio"/> MM

Adjustable accessories

<input type="radio"/> Reflective material
<input type="radio"/> Adhesive badge holder
<input type="radio"/> Detachable badge holder
<input type="radio"/> Protective ear muffs
<input type="radio"/> Headlamp
<input checked="" type="radio"/> Chin strap* 2-point (cotton, leather or textile)
<input type="radio"/> Chin strap* 4-point (textile)
<input type="radio"/> "Forester" mesh
<input type="radio"/> Protective visor
<input type="radio"/> Spare glass
<input type="radio"/> Bulb holder and grommet (not compatible with the 440 Va option)

*Special anchorage for our models



CASQUETTE DE PROTECTION

TALIACAP®

Data sheet - **English** version
Personal Protection Equipment



CE - EN 812

Main applications :

- Agro-food industry.
- Visitors.

Product advantages :

- Very light.
- Comfortable, stays firmly in place thanks to the textile lining.
- Traceability : date of manufacture under the helmet peak.



Marking (e.g.: company logo)

Screen printing

<input checked="" type="radio"/> Front	L 50 x H 50 mm
<input checked="" type="radio"/> Side	L 75 x H 15 mm
<input type="radio"/> Back	-

TALIA
PLAST

SOFOP S.A.S taliaplast®
3 route de la Torse
44550 Montoir de Bretagne - France

Société Française d'Outils Professionnels
SAS au capital de **10 000 000 Euros**
006 780 514 R.C.S. Saint-Nazaire
SIREN 006 780 514 - APE 2229 B
N° TVA FR 72 006 780 514
Identifiant EORI : FR 006 780 514 00037

www.taliaplast.com

Export DPT

GRAND EXPORT / OVERSEAS Area
e-mail: export@taliaplast.com
Phone: +33 (0) 251 16 60 86

EUROPE / EUROPE Area
e-mail: sales@taliaplast.com
Phone: +33 (0) 251 16 61 02








Commercial France

Tél. 02 51 16 60 60
e-mail : commercialfrance@taliaplast.com

Key :

- Available in the range
- ◐ Option possible (contact us)
- Not available

Colours

	<input checked="" type="radio"/> White
	<input type="radio"/> Yellow P116C
	<input type="radio"/> Green P347C
	<input type="radio"/> Blue P2935C
	<input type="radio"/> Orange P179C
	<input type="radio"/> Red P1797C
	<input type="radio"/> Neon Yellow

Cradle

Description		
<input type="radio"/> RB Web plastic	<input checked="" type="radio"/> TB Textile	<input type="radio"/> RB Monobloc plastic

Number of Anchorage points		
<input type="radio"/> 4 Pts	<input type="radio"/> 4 Pts	<input type="radio"/> 4 Pts
<input type="radio"/> 6 Pts	<input checked="" type="radio"/> 6 Pts	<input type="radio"/> 6 Pts

Standard adjustment (size 53 - 61 cm)		
<input type="radio"/> RB	<input checked="" type="radio"/> TB	<input type="radio"/> RB

Ratchet adjustment (size 53 - 61 cm)		
<input type="radio"/> RB	<input type="radio"/> TB	<input type="radio"/> RB

Components		
<input type="radio"/> PE BD	<input checked="" type="radio"/> PE BD	<input type="radio"/> PE BD
<input type="radio"/> PE MD	<input checked="" type="radio"/> PE MD	<input type="radio"/> PE MD

Sweatband		
<input type="radio"/> 20 cm	<input type="radio"/> 20 cm	<input type="radio"/> 20 cm
<input type="radio"/> 37 cm	<input checked="" type="radio"/> 37 cm	<input type="radio"/> 37 cm
<input type="radio"/> 40 cm	<input type="radio"/> 40 cm	<input type="radio"/> 40 cm

Shell material

<input checked="" type="radio"/> HDPE (High density polyethylene)
<input type="radio"/> ABS

Weight

390 g

Life expectancy

(from the date of manufacture and in normal conditions of storage and use)

<input type="radio"/> 3 years
<input checked="" type="radio"/> 5 years

Ventilated sides

<input type="radio"/> Adjustable
<input type="radio"/> Non-adjustable

Temperature resistance

<input type="radio"/> -10°C	<input checked="" type="radio"/> -20°C	<input type="radio"/> -30°C	<input checked="" type="radio"/> +50°C
-----------------------------	--	-----------------------------	--

Electrical insulation (non-vented only)	
<input checked="" type="radio"/>	Electrical class 0 → Alternating voltage up to 1000 V or direct voltage up to 1500 V : electrical insulation for use on low voltage installations.

Protection against molten metal splash	
<input checked="" type="radio"/>	MM

Adjustable accessories

<input type="radio"/> Reflective material
<input type="radio"/> Adhesive badge holder
<input type="radio"/> Detachable badge holder
<input checked="" type="radio"/> Protective ear muffs
<input checked="" type="radio"/> Headlamp
<input type="radio"/> Chin strap* 2-point (cotton, leather or textile)
<input checked="" type="radio"/> Chin strap* 4-point (textile)
<input checked="" type="radio"/> "Forester" mesh
<input checked="" type="radio"/> Protective visor
<input type="radio"/> Spare glass
<input checked="" type="radio"/> Bulb holder and grommet (not compatible with the 440 Va option)

*Special anchorage for our models



PROTECTIVE HELMET

ALBATROS®

OPUS® erector version

Data sheet - **English** version
Personal Protection Equipment




CE - EN 397
CE - EN 50365

Main applications :

- Working at height.

Product advantages:

- Reduced peak.
- Electrical insulation :  Electrical class 0 : alternating voltage up to 1000 V or direct voltage up to 1500 V (non-vented helmet).
- 4-point chin strap.
- Maximum comfort: adjustable textile lining and 37 cm Sweatband.
- Traceability : date of manufacture and batch identification marked under the helmet peak.



Marking (e.g.: company logo)

Screen printing	
<input checked="" type="radio"/> Front	L 45 x H 40 mm
<input checked="" type="radio"/> Side	L 75 x H 15 mm
<input type="radio"/> Back	-



SOFOP S.A.S taliplast®
3 route de la Torse
44550 Montoir de Bretagne - France

Société Française d'Outils Professionnels
SAS au capital de **10 000 000 Euros**
006 780 514 R.C.S. Saint-Nazaire
SIREN 006 780 514 - APE 2229 B
N° TVA FR 72 006 780 514
Identifiant EORI : FR 006 780 514 00037

www.taliplast.com

Export DPT

GRAND EXPORT / OVERSEAS Area
e-mail: export@taliplast.com
Phone: +33 (0) 251 16 60 86

EUROPE / EUROPE Area
e-mail: sales@taliplast.com
Phone: +33 (0) 251 16 61 02

Commercial France

Tél. 02 51 16 60 60
e-mail : commercialfrance@taliplast.com

Key :

- Available in the range
- ◐ Option possible (contact us)
- Not available

Data sheet - English version
Personal Protection Equipment

Coloris

64 possible associations of colours

Shell material

HDPE (high-density polyethylene)
 ABS

Visor material

HDPE (high-density polyethylene)
 ABS

Life expectancy

(from the date of manufacture and in normal conditions of storage and use)

3 years
 5 years

Weight without eyewear

450 g

with eyewear

500 g

Temperature resistance

-10°C -20°C -30°C +50°C

Electrical insulation (non-vented only)

Electrical class 0 → Alternating voltage up to 1000 V or direct voltage up to 1500 V : electrical insulation for use on low voltage installations.

Protection against molten metal splash

MM

Adjustable accessories

- Reflective material
- Adhesive badge holder
- Detachable badge holder
- Protective ear muffs
- Headlamp
- Chin strap* 2-point (cotton, leather or textile)
- Chin strap* 4-point (textile)
- "Forester" mesh
- Protective visor
- Spare glass
- Bulb holder and grommet (not compatible with the 440 Va option)

* Special anchorage for our models



Cradle

Description

RB web plastic TB fabric RB RB monobloc plastic

Number of anchorage points

4 Pts 4 Pts 4 Pts
 6 Pts 6 Pts 6 Pts

Ratchet adjustment (from sizes 53-61 cm)

RB TB RB

Sweatband

20 cm 20 cm 20 cm
 37 cm 37 cm 37 cm
 40 cm 40 cm 40 cm

Ventilated sides

Adjustable
 Non-adjustable



Helmet :

CE - EN 397
 CE - EN 50365

Integrated eyewear safety :

CE - EN 166

Main applications :

- Industrial production and construction.

Product advantages :

- Traceability : date of manufacture and batch identification marked under the helmet peak.
- Excellent impact and penetration resistance.
- An accurate and easily adjustable wheel ratchet - no clutch necessary - for a perfect set up of the helmet on the head. The wheel ratchet is positioned on the neck to create a firm comfort fit with added security in the event of shocks.
- Textile cradle for more comfort.

Model with eyewear

- Polycarbonate, transparent, anti-shock and anti-rays, maximum coverage.
- Side buttons allow for an easier eyewear adjustability while wearing gloves.
- Easily retractable clear screen for maximum eye protection.
- Compatible with the majority of glasses.

Marking (e.g.: company logo)

Screen printing (only one colour)

<input checked="" type="radio"/> Front	L 50 x H 40 mm
<input checked="" type="radio"/> Side	L 60 x H 20 mm
<input type="radio"/> Back	-

Key :

- Available in the range
- Option possible (contact us)
- Not available



SOFOP S.A.S taliaplast®
3 route de la Torse
44550 Montoir de Bretagne - France

Société Française d'Outils Professionnels
SAS au capital de 10 000 000 Euros
006 780 514 R.C.S. Saint-Nazaire
SIREN 006 780 514 - APE 2229 B
N° TVA FR 72 006 780 514
Identifiant EORI : FR 006 780 514 00037

www.taliaplast.com

Export DPT

GRAND EXPORT / OVERSEAS Area
e-mail: export@taliaplast.com
Phone: +33 (0) 251 16 60 86

EUROPE / EUROPE Area
e-mail: sales@taliaplast.com
Phone: +33 (0) 251 16 61 02

Commercial France
Tél. 02 51 16 60 60
e-mail : commercialfrance@taliaplast.com



The new **bi**-coloured generation



www.taliaplast.com



La FRENCH FAB

